


## 4 Parameters Sonde with Wiper -For Aquaculture



### AQUA200- a 4 parameters sonde for aquaculture application



The AQUA200 water platform is rugged in aquaculture water, delivering accurate, reliable data in an easy-to-use for end fisherman. Base sonde configuration includes optical dissolved oxygen(optical DO), pH, ORP, temperature and wiper system.

#### Key Advantages:

- Easy to use - support RS485 and Modbus protocol
- Easy to maintain - auto wiper system for antifouling for months, optical DO drift <1% per year, robust pH, ORP and reference electrode.
- Materials - Right housing materials for aquaculture
- Low cost - all made in China
- Strong technical capability - own all technologies including nano-materials, optical sensing and software algorithm

# Specification



## Technical Specifications

Measurement Method	DO: EPA-approved : 1002-8-2009, 1003-8-2009, 1004-8-2009
	pH: Std. Methods 4500-H+/EPA 150.2
	ORP: Std. Methods 2580
Range	DO: 0-20mg/L Or 0-200% Sat., pH: 0-14, ORP: -1200~+1200mV, Temperature: -5~50°C
Resolution	DO: 0.01mg/L Or 0.01% Sat., pH: 0.01, ORP: 1mV
Accuracy	DO: +/-0.3mg/L Or 3% FS, pH +/-0.2@10~30°C, ORP +/-10mV, Temperature +/-0.3°C@5~50°C
Operating temperature	0~45°C
Storage Temperature	-10~50°C
Clean system	Auto wiper system is optional
Warranty	1 year (pH and reference electrode 0.5 year)
Depth	IP68, 10m Max
Power	12V 60mA (normal)
Output	RS485 and Modbus protocol
Materials	Titanium( mariculture ) or SS316( freshwater aquaculture), POM, Nylon, PUR
Dimensions	Length 275mm, diameter 69mm, weight 0.8kg in air without cable
Field life*	DO 2 years or greater, pH and ORP 1 year or greater, temperature 2 years or greater, wiper system 1.5 year or greater
Recommended Calibration Frequency*	DO 6 months, pH and ORP 8-12 weeks, temperature 1 year, wiper system inspection 12 months.

Note: \*Field life and calibration frequency dependent on site conditions.

## BroadSensor Technologies Co.,Ltd

Addr: 3rd Floor, Block A, 80 Xinze Road,  
Suzhou Industrial Park, China 215123  
Tel: +86-512-88960831  
Fax: +86-512-62988329  
Email: [sales@broadsensor.com](mailto:sales@broadsensor.com)  
Web: [www.broadesnsor.com](http://www.broadesnsor.com)

2018. All right reserved

### Order info:

PN: 610112 Optical DO SS316 shell  
PN: 941622 Mother body/sonde  
PN: 741622 Wiper sub-system  
PN: 723810-O ORP electrode  
PN: 723810-P pH electrode  
PN: 723810-R Reference electrode